



- Wide operating voltage range: 10~30VDC or 90~250VAC
- All models with the operating indicator for easy identified
- Good waterproof, conforming to IP-66 requirement
- Output method : NPN, PNP, AC - 2 wires, AC - 3 wires

Outline Dimension (Unit:mm)	Model No.	Output Status	Output Method	Sensing Distance	Mounting Method	Operating Voltage	Response Frequency	
	GEN-1705-E1	NO	NPN	5mm	Non-Flushed	10-30VDC	600Hz	
	GEN-1705-E2	NC						
	GEN-1705-P1	NO	PNP					
	GEN-1804-E1	NO	NPN	4mm	Non-Flushed	10-30VDC	500Hz	
	GEN-1804-E2	NC						
	GEN-1804-P1	NO	PNP				90-250VAC	15Hz
	GEN-1804-A1	NO	AC - 2 wire					
	GEN-2507-E1	NO	NPN	7mm	Non-Flushed	10-30VDC	500Hz	
	GEN-2507-E2	NC						
	GEN-2507-P1	NO	PNP				90-250VAC	15Hz
	GEN-2507-A1	NO	AC - 2 wire					
	GEN-2507-3A1	NO	AC - 3 wire				30Hz	
	GEN-2507-3A2	NC	AC - 3 wire					
	GEN-3010-E1	NO	NPN	10mm	Non-Flushed	10-30VDC	500Hz	
	GEN-3010-E2	NC						
	GEN-3010-P1	NO	PNP				90-250VAC	15Hz
	GEN-3010-A1	NO	AC - 2 wire					
	GEN-3010-3A1	NO	AC - 3 wire				30Hz	
	GEN-3010-3A2	NC	AC - 3 wire					
	GLX-1202-E1	NO	NPN	2mm	Flushed	10~30VDC	800Hz	
	GLX-1202-E2	NC						
	GLX-1202-P1	NO	PNP				1K Hz	
	SC1202-KP2	NO / NC	NPN / PNP					
	SC1202-A	NO	SCR				90~260VAC	20Hz
	GLX-1204-E1	NO	NPN	4mm	Non-Flushed	10~30VDC	500Hz	
	GLX-1204-E2	NC						
	GLX-1204-P1	NO	PNP				90~260VAC	20Hz
	SC1204-KP2	NO / NC	NPN / PNP					
	SC1204-A	NO	SCR					
	GLX-1805-E1	NO	NPN	5mm	Flushed	10-30VDC	400Hz	
	GLX-1805-E2	NC						
	GLX-1805-P1	NO	PNP				90-250VAC	20Hz
	GLX-1805-A1	NO	AC - 2 wire					
	GLX-1805-3A1	NO	AC - 3 wire				40Hz	
	GLX-1805-3A2	NC	AC - 3 wire					
	GLX-1808-E1	NO	NPN	8mm	Non-Flushed	10-30VDC	300Hz	
	GLX-1808-E2	NC						
	GLX-1808-P1	NO	PNP				90-250VAC	20Hz
	GLX-1808-A1	NO	AC - 2 wire					
	GLX-1808-3A1	NO	AC - 3 wire				40Hz	
	GLX-1808-3A2	NC	AC - 3 wire					
	GLX-3010-E1	NO	NPN	10mm	Flushed	10-30VDC	200Hz	
	GLX-3010-E2	NC						
	GLX-3010-P1	NO	PNP				90-250VAC	20Hz
	GLX-3010-A1	NO	AC - 2 wire					
	GLX-3010-3A1	NO	AC - 3 wire				40Hz	
	GLX-3010-3A2	NC	AC - 3 wire					
	GLX-3015-E1	NO	NPN	15mm	Non-Flushed	10-30VDC	100Hz	
	GLX-3015-E2	NC						
	GLX-3015-P1	NO	PNP				90-250VAC	20Hz
	GLX-3015-A1	NO	AC - 2 wire					
	GLX-3015-3A1	NO	AC - 3 wire				40Hz	
	GLX-3015-3A2	NC	AC - 3 wire					